


**TaiShan**  
SINCE **1978**

**TAISHAN** | **2025**

**BALL EQUIPMENT**



Taishan Sports

TaiShan Sports Brings Sports Enjoyment To The World

# CATALOGUE



01

## TAISHAN SPORTS

About Us	02
Company Info	03
Certifications	04

02

## BALL EQUIPMENT SERIES

Basketball	07
Football	25
Volleyball	33
Table Tennis	39
Badminton	43
Tennis	47
Padel	53
LED Display Screen	57
Venue Seat Series	63

03

## EVENT CASES

Gymnasium	85
Exhibitions	86

# 01

## TAISHAN SPORTS

About Us


02

Company Info

03

Certifications

04



### —— About Us ——

One-Stop Global Sports Solution Service



#### Zero Complaints

We have served more than 1,000 international and domestic top sports events including 6 Olympic Games and 3 Youth Olympic Games, with "Zero Complaints".



#### Zero Breakdowns

As the world's top event service provider, We take high product quality seriously and will settle for nothing less than equipment "Zero Breakdown".



#### Zero Faults

With "Zero Failure" service level and the value pursuit of "no small matters in game" in mind, we have built the world's leading sports brand.

## Company Info



As a world-famous sports equipment manufacturer and seller, Taishan Sports is now leading China's sports industry. It has successfully served multiple major sports events, such as Olympic Games, Youth Olympic Games, Asian Games, FISU World University Games, and National Games, using its pioneering CD2S (Consult, Design, Supply, and Service) service model for major sports events. Credited as "an Olympic miracle" by the former IOC president Jacques Rogge, Taishan Sports' high standard service with "Zero Faults, Zero Breakdowns, Zero Complaints" has made itself a proud national brand.

Entitled as National Sports Goods Engineering Technology Research Center, National Industrial Design Center, National Enterprise Technology Center, and Postdoctoral R&D Station, Taishan Sports is fully capable of conducting R&D of and testing on national level sports goods. With nearly 300 patents in hand, it has led and participated in setting over 60 domestic and international sports industry standards. More than 100 of its products have been certified by FIG, IJF, WT, UWW, WA, and IWUF, and its XPE multifunctional sports mats are listed on the China Torch Program. With all of its competitive gymnastic equipment certified by FIG, Taishan Sports has unprecedently adopted carbon fiber composite in production. At the same time, it continues to popularize gymnastic equipment and has come up with products for children and the elderly, creating "Taishan quality shared around the globe". Meanwhile, Taishan Sports is always insisting on continuous technological innovation and material upgrading in other fields.

## Certifications



FIBA Certification  
( 3x3 Basketball Stand )



FIBA Certification  
( including 5 certified basketball stands )



# 02

## BALL EQUIPMENT SERIES

Basketball  
07-24

Football  
25-32

Volleyball  
33-38

Table Tennis  
39-42


Badminton  
43-46

Tennis  
47-52

Padel  
53-56

LED Display Screen  
57-62

Venue Seat Series  
63-83



# Basketball

## Ball Equipment Series

### TQ1461 Advanced Competition Elastic Balance Basketball Stand

Model: TQ1461

1. Basket Height: 3.05m
2. Extension arm size: 3.25m
3. Backboard size: 1800mm×1050mm
4. Basket: φ450mm

5. Backboard material: Tempered glass
6. Basketball stand color option: 

7. Protective pads colors are optional and images can be customized: 

8. Backboard cover colors available: 

9. Using in indoor environment. Optional 24 second timer. There should be more than 4.2m space outside the end line of the site.

With elastic balance structure and spring auxiliary lifting, it can be moved with manual assistance.



COMPETITION  
LEVEL 1&2

### TQ1461A With electro-hydraulic structure and electro-hydraulic auxiliary lifting

### TQ1461B (no international certification) With manual-hydraulic structure and manual-hydraulic auxiliary lifting

1. Basket Height: 3.05m

2. Extension arm size: 3.25m

3. Backboard size: 1800mm×1050mm

4. Basket: φ450mm

5. Backboard material: Tempered glass

6. Basketball stand color option: 

7. Protective pads colors are optional and images can be customized: 

8. Backboard cover colors available: 

9. Using in indoor environment. There should be more than 4.2m space outside the end line of the site. With positioning pin, ground anchor, it can be moved with manual assistance.



## Competition Elastic Balance Basketball Stand

Model: TQ1462

1. Basket Height: 3.05m
2. Extension arm size: 3.25m
3. Backboard size: 1800mm×1050mm
4. Basket: φ450mm
5. Backboard material: Tempered glass
6. Basketball stand color option: 
7. Protective pads colors are optional and images can be customized: 



7. Protective pads colors are optional and images can be customized:



8. Backboard cover colors available: 

9. Using in indoor environment. Optional 24 second timer. There should be more than 4.2m space outside the end line of the site. With elastic balance structure and spring auxiliary lifting, it can be moved with manual assistance



## 3x3 Basketball Stand

Model: TQ1463

1. Basket Height: 3.05m
2. Extension arm size: 2.25m
3. Backboard size: 1800mm×1050mm
4. Basket: φ450mm
5. Backboard material: Tempered glass
6. Basketball stand color option: 
7. Protective pads colors are optional and images can be customized: 

8. Backboard cover colors available: 

9. It can be used in outdoor environment. Optional 12 second timer. There should be more than 3.2m space outside the end line of the site. With elastic balance structure and spring auxiliary lifting, it can be moved with manual assistance.



3x3

Approval Level 1

## Intermediate Training Electro-hydraulic Basketball Stand

Model: TQ1462A/1

1. Basket Height: 3.05m
2. Extension arm size: 2.25m
3. Backboard size: 1800mm×1050mm
4. Basket: φ450mm
5. Backboard material: Tempered glass
6. With electro-hydraulic structure and electro-hydraulic (220V) auxiliary lifting, it can be moved with manual assistance.
7. Optional 24 second timer.
8. There should be more than 3.2m space outside the end line of the site.



## Luxury Fixed Single Post Basketball Stand

Model: TQ1464

1. Basket Height: 3.05m
2. Extension arm size: 1.8m
3. Backboard size: 1800mm×1050mm
4. Basket: φ450mm
5. Backboard material: Tempered glass
6. Basketball stand color option: 
7. Protective pads colors are optional and images can be customized: 

8. Backboard cover colors available: 

9. Using in indoor environment. Embedded fixed structure. There should be more than 1.15m space outside the end line of the site.



Approval Level 2

**TQ1465****Intermediate Training Elastic Balance Basketball Stand**

1. Basket Height: 3.05m
2. Extension arm size: 2.25m
3. Backboard size: 1800mm×1050mm
4. Basket: φ450mm
5. Backboard material: Tempered glass
6. With elastic balance structure and spring auxiliary lifting, it can be moved with manual assistance.
7. Optional 24 second timer and ground anchor.
8. There should be more than 3.2m space outside the end line of the site.

**TQ1465/1****Intermediate Training Elastic Balance Basketball Stand**

1. Basket Height: 3.05m
2. Extension arm size: 3.25m
3. Backboard size: 1800mm×1050mm
4. Basket: φ450mm
5. Backboard material: Tempered glass
6. With elastic balance structure and spring auxiliary lifting, it can be moved with manual assistance.
7. Optional 24 second timer and ground anchor.
8. There should be more than 4.2m space outside the end line of the site.

**TQ1465A****Intermediate Training Electro-hydraulic Basketball Stand**

Using in indoor environment.

1. Basket Height: 3.05m.
2. Extension arm size: 3.25m.
3. Backboard size: 1800mm × 1050mm.
4. Material: tempered glass.
5. Basket: φ450mm.
6. With electro-hydraulic structure auxiliary lifting, it can be moved with manual assistance.
7. Electric hydraulic system voltage 220V, power 1.5Kw.
8. Optional 24 second timer.
9. There should be more than 4.2m space outside the end line of the site.

**TQ1465A/1****Intermediate Training Electro-hydraulic Basketball Stand**

Using in indoor environment.

1. Basket Height: 3.05m.
2. Extension arm size: 2.25m.
3. Backboard size: 1800mm × 1050mm.
4. Material: tempered glass.
5. Basket: φ450mm.
6. With electro-hydraulic structure auxiliary lifting, it can be moved with manual assistance.
7. Electric hydraulic system voltage 220V, power 1.5Kw.
8. Optional 24 second timer.
9. There should be more than 3.2m space outside the end line of the site.

**TQ1465B****Intermediate Training Manual-Hydraulic Basketball Stand**

Using in indoor environment.

1. Basket Height: 3.05m.
2. Extension arm size: 3.25m.
3. Backboard size: 1800mm × 1050mm.
4. Material: tempered glass.
5. Basket: φ450mm.
6. With manual-hydraulic structure auxiliary lifting, it can be moved with manual assistance.
7. Optional 24 second timer.
8. There should be more than 4.2m space outside the end line of the site.

**TQ1465B/1****Intermediate Training Manual-Hydraulic Basketball Stand**

Using in indoor environment.

1. Basket Height: 3.05m.
2. Extension arm size: 2.25m.
3. Backboard size: 1800mm × 1050mm.
4. Material: tempered glass.
5. Basket: φ450mm.
6. With manual-hydraulic structure auxiliary lifting, it can be moved with manual assistance.
7. Optional 24 second timer.
8. There should be more than 3.2m space outside the end line of the site.

# COMPETITION LEVEL 2





**TQ2357**  
**Youth Manual Lifting Basketball Stand**

**TQ2357/1**  
**Youth Electric Lifting Basketball Stand**

1. Basket Height: 1.4 - 3.05m
2. Extension arm size: 0.7 - 1.1m
3. Backboard size: 1200mm×800mm
4. Basket: φ450mm
5. Backboard material: Tempered glass
6. Using in indoor environment, and it can be moved with manual assistance.



## COMPETITION LEVEL 1&2



**Competition Intelligent Self-propelled Basketball Stand**

Model: TQ3.25ZN

1. Extension arm size: 3.25m
2. Backboard size: 1800mm×1050mm
3. Basket: φ450mm
4. Accessories: Standard 24-second timer
5. Base dimension: Length 2300 × Width 1120 × Front height 733 × Rear height 515mm
6. Material: High transparent tempered glass backboard (with high light signal strip), the basketball arm folding and self-moving can be achieved by wireless remote control



## COMPETITION LEVEL 1&2



### 2.25m Concaved Box Basketball Stand

Model: TQ2.25XT

1. Extension arm size: 2.25m
2. Backboard size: 1800mm×1050mm
3. Basket: φ450mm
4. Material: The extension arm of the basketball stand is welded with 160×80×3mm rectangular high-quality carbon steel pipe, which effectively improves the overall stiffness of the basketball stand. The front and rear columns of the basketball stand are welded with 150×3mm rectangular high-quality carbon steel pipes, and the base is welded with 40×20×3mm rectangular high-quality carbon steel pipes and 3mm high-quality carbon steel plates. At the same time, the base is equipped with counterweight. The overall coating process has good anti-corrosion to ensure that the basketball stand can be used outside the room for a long time.



### Hydraulic-like Basketball Stand

Model: TQ2365

1. Extension arm size: 2.25m
2. Backboard size: 1800×1050m
3. Backboard material: Tempered glass backboard

Model: TS-1005/1

1. Extension arm size: 2.25m
2. Backboard size: 1800×1050m
3. Backboard material: SMC backboard



### Detachable Basketball Stand

Model: TQW0383

1. Extension arm size: 2.25m
2. Backboard size: 1800×1050m
3. Backboard material: Tempered glass backboard

Model: TQW0383/1

1. Extension arm size: 2.25m
2. Backboard size: 1800×1050m
3. Backboard material: SMC backboard



### Movable Basketball Stand

Model: TQ3040A/2


1. Extension arm size: 2.25m
2. Basket Height: 3.05m
3. Specification: 2×1m box
4. Backboard material: Backboard material: Tempered glass backboard(three-point support)



### One-arm Basketball Stand

Model: TSTQL3061

1. Extension arm size: 2.25m
2. Extension Basket Height: 3050mm
3. 180mm Square Tube Column
4. Backboard material: SMC backboard



### Movable Basketball Stand

Model: TSTQL3040

1. Extension arm size: 2.5m
2. Specification: 4865mm×1800mm×3950mm
3. Backboard material: SMC backboard

### One-arm Basketball Stand

Model: TQ3061/2

1. Extension arm size: 2.25m
2. Extension Basket Height: 3050mm
3. 180mm Square Tube Column
4. Backboard material: Tempered glass backboard (three-point support)



### Four-Arm Basketball Stand

Model: TQ2387

1. Extension arm size: 1.8m
2. Basket Height: 2050/2350/2700/3050mm
3. Backboard material: Tempered glass



### Mini Backboard Basketball Stand

Model: TSQL3039

1. Extension arm size: 1.5m
2. Basket Height: 3050mm
3. Backboard material: SMC backboard
4. Specification:  $\varnothing 140$ mm column



### Buried Basketball Stand

Model: TSQL3041

1. Extension arm size: 1.8m
2. Basket Height: 3050mm
3. Backboard material: SMC backboard
4. Specification:  $\varnothing 165$ mm column



### No-backboard Basketball Stand

Model: TQW0384

1. Extension arm size: Ring height 3050mm
2. Material: Steel, Removable



### FIBA Competition Backboard

Model: TQ1461.08

1. Specification: 1800mm×1050mm

2. Material: Tempered glass



### Spring Basketball Hoop

Model: TQ3200.11

1. Specifications: φ450mm, Mounting hole spacing: 126mm × 107mm

2. Materials: Made of 18mm high-strength carbon steel with a built-in high-elasticity spring for excellent shock absorption. Features a premium thickened steel base to increase the hoop's support area, ensuring sturdiness and durability.

Note: Includes a basketball hoop net.

### Tempered Glass Backboard (three-point support)

Model: TQ3040/2.03

1. Specification: 1800mm×1050mm

2. Material: Tempered glass




### Basketball Hoop

Model: TQ1461.09

1. Specifications: φ450mm, Mounting hole spacing: 126mm × 107mm

2. Materials: Made of 18mm high-strength carbon structural steel with a built-in spring, ensuring superior shock absorption, in line with FIBA requirements.

Note: Official FIBA-approved basketball stand.




### SMC Backboard

Model: TQ3040.07

1. Specification: 1800mm×1050mm

2. Material: SMC



### SMC Fan-shaped Backboard

Model: TQ3039.00-01

Material: SMC



### Basketball Net

Model: TQW0870

1. Specification: Wire diameter: 5mm, Flat rope: 7mm

2. Material: Material: Polyester, total Length: 50 cm, with 12-loop (minus 2-loop variant) and stitched joints, and anti-rebound construction.

## Basketball Net

Model: TQ3200.11-04

Material: polyester, wear-resistant and anti-aging



## Suspended Substitution Cards

Model: TQW0041

1. Specification: 240mm×160mm×4mm

2. Material: PVC double-sided



## Ball Storage Cart

Model: TQW0839

1. Specification: 880mm×650mm×650mm

2. Material: Aluminum alloy frame, Oxford fabric

3. Weight: 4.2kg

4. Capacity: Spacious interior storage



## Basketball

Model: TQW0011-05, TQW0011-06, TQW0011-07

1. Specification: 5#, 6#, 7#

2. Material: Microfiber



## Ball Folding Cart

Model: TQW0385

1. Specification: 900mm×600mm×790mm

2. Material: Steel



## Basketball Scoreboard

Model: TQW0840

1. Specification: 1730mm×850mm×660mm

2. Material: Material: Premium steel frame with PVC manual flip-score mechanism.

# Football

## Ball Equipment Series



### Football Goal (11v11)

Model: TQ2383

1. Specification: Inner Width 7320mm  
Inner Height 2440mm  
Lower Depth 3000mm  
Upper Depth 2400mm
2. Material: Aluminum alloy

Model: TSTQ3008

1. Specification: Inner Width 7320mm  
Inner Height 2440mm  
Lower Depth 3000mm  
Upper Depth 2400mm
2. Material: Steel tube



### Football Goal (7v7)

Model: TQ2380

1. Specification: Inner Width 5500mm  
Inner Height 2000mm  
Lower Depth 2000mm  
Upper Depth 1400mm
2. Material: Aluminum alloy

Model: TSTQ3007

1. Specification: Inner Width 5500mm  
Inner Height 2000mm  
Lower Depth 2000mm  
Upper Depth 1400mm
2. Material: Steel tube



### Football Goal (5v5)

Model: TQ2379

1. Specification: Inner Width 3000mm  
Inner Height 2000mm  
Lower Depth 1500mm  
Upper Depth 900mm
2. Material: Aluminum alloy

Model: TSTQ3006

1. Specification: Inner Width 3000mm  
Inner Height 2000mm  
Lower Depth 1500mm  
Upper Depth 900mm
2. Material: Steel tube



### Embedded Football Goal (11v11)

Model: TQ2369

1. Specification: 7320mm×2440mm
2. Material: Aluminum alloy

Model: TQ2399

1. Specification: Inner Width 7320mm  
Inner Height 2440mm  
Lower Depth 3000mm  
Upper Depth 3000mm
2. Material: Steel tube



## Football Tunnel

Model: TQW0533

1. Specification: 12000mm×2500mm×2300mm
2. Material: Combined, stainless steel, PVC awning.

Model: TQW0533/1

1. Specification: 12000mm×2500mm×2300mm
2. Material: Telescopic, stainless steel, PVC awning.



## Football Training Hurdle I

Model: TSWZQ112

1. Specification: Height 150mm, 230mm, 300mm, 400mm, 500mm
2. Material: Eco-friendly PVC material, riot-proof, crack-proof and weather-proof, reinforced and wear-resistant, stable and beautiful



## Football Training Hurdle II

Model: TSWZQ109

1. Specification: Height can be 160mm, 240mm, 310mm
2. Material: Environmental-friendly PVC material, antioxidation, not easy to loose, color is bright.

## Sensitive Ladder

Model: TSWZQ104-01  
TSWZQ104-02

Specification: 3000mm 6 sections  
4000mm 8 sections

Material: High-density webbing + eco-friendly PP, easy to stretch freely, fast, soft and strong.



## Football Marker Cone

Model: TSWZQ103-01  
TSWZQ103-02

Specification: 180mm high  
230mm high

Material: Eco-friendly LDPE material that allows cone's shape to change naturally when pressed and is hard to break.

## Football Net

Model: ZSH16 (11 v 11),  
ZSH18 (7 v 7), ZSH181 (5 v 5)

1. Specification: Standard
2. Material: High quality polyester and nylon material, weathering, rain, sun, impact resistance, durable



## Football

Model: TQW0012-04  
TQW0012-05

Specification: 4#  
5#

Material: High quality PU



## Football Disk Dish

Model: TSWZQ102

1. Specification: Bottom dia:195mm, upper dia: 95mm, height: 80mm
2. Material: Imported LDPE material, with bright colors and good stability, which is sturdy and durable.



### Football Reserve Seats III

Model: TS-Z03

1. Specification: H Total height: 1860 mm, total depth: 1400 mm.
2. Material: Aluminum alloy profile, PC Solid sheets



### Simulating 5-man Football Wall (movable)

Model: TSWZQ108

1. Specification: Height 1760mm, single widest part 460mm
2. Material: Aluminum alloy



### Football Simulate Single Wall (fixed)

Model: TSWZQ107

1. Specification: Height 1760mm, widest part 460mm
2. Material: Aluminum alloy



### Football Reserve Seats IV

Model: TQW0843

1. Specification: Total height: 2000 mm, total depth: 750 mm.
2. Material: Stainless steel pipe, PC Solid sheets



### Football Handflag

Model: TQW0373

1. Specification: 450mm×350mm
2. Material: Aluminum alloy



### Football Red and Yellow Cards

Model: TSWZQ113

1. Specification: 175mm×118mm
2. Material: Thickened PVC sheet, PU leather wallet

## Football Tactic Board

Model: TSWZQ110  
 1. Specification: 615mm×460mm  
 2. Material: Magnetic board, no assembly required. 26 magnetic numbers, adjustable height, rewritable battle plate.




## Football Coaching Map

Model: TSWZQ111  
 1. Specification: 290mm×235mm×320mm  
 2. Material: Magnetic board, foldable design, with 28 magnetic chess pieces, strong magnetic, easy to carry.

## Football Scoreboard

Model: TQW0323  
 1. Specification: 1730mm×850mm×660mm  
 2. Material: Steel frame, PVC card, height adjustable



## Football Corner Flag (water injection based)

Model: TSWZQ105  
 1. Specification: Height 1500mm, base diameter φ200mm  
 2. Material: Imported eco-friendly PP material, good toughness, hard to break.



## Football Corner Flag (fixed)

Model: TSWZQ106  
 1. Specification: Height 1500mm  
 2. Material: Imported eco-friendly PP material, good toughness, hard to break



## Football Training Pole

Model: TSWZQ101-01 Specification: 1000mm  
 TSWZQ101-02 1500mm

Material: ABS environmental-friendly material bright color, good toughness, no deformation, wear resistance.

# Volleyball

## Ball Equipment Series



### Movable Volleyball Net Pole (manual lifting)

Model: TQW0374

1. Specification: Box size: 1500mm×750mm×300mm  
Pole height range: 1900-2430 mm
2. Material: Aluminum alloy

Model: TSTQ3003

1. Specification: Box size: 1586×670×353mm  
Center height of net: 2220mm/2480mm  
Pole height range: 1900-2430 mm
2. Material: Steel tube



### Movable Badminton & Volleyball Combo Pole

Model: TQ2370

1. Specification: 12970×670×1454/1664/1920/2120mm
2. Material: It is used for volleyball and badminton competitions at schools and youth clubs.



### Embedded Volleyball Post Protector

Model: TQ2699/3

(Compatible with TS-YPW-013, TS-YPW-0131)



### Volleyball Net Height Measurer

Model: PQ20

Material: Aluminum alloy

### Fixed Volleyball Net Pole (manual lifting)

Model: TS-YPW-013

1. Specification: Outer diameter of pole 89mm  
height range 1900mm-2430mm

2. Material: Aluminium alloy

Model: TS-YPW-0131

1. Specification: Outer diameter of pole 89mm  
height range 1900mm-2430mm

2. Material: Steel tube




### Fixed Volleyball Net Pole (spring lifting)

Model: TS-YPW-0141

1. Specification: Outer diameter of pole 89mm  
height range 1900mm-2430mm

2. Material: Steel tube




### Volleyball Substitution Cards

Model: TQW0833  
 1. Specification: 240mm×160mm×4mm  
 2. Material: PVC



### Competition Volleyball

Model: TQW0013  
 1. Specification: 5#  
 2. Material: Microfiber



### Volleyball Scoreboard

Model: TQW0832  
 1. Specification: 1730mm×850mm×660mm  
 2. Material: Steel frame, PVC board



### Volleyball Referee Chair

Model: TQW0831  
 1. Specification: 1000mm×1000mm×2400mm  
 2. Material: Steel; height adjustable



### Volleyball Net (normal)

Model: PQ16  
 1. Specification: 9500mm×1000mm  
 wire hole 100mm×100mm  
 Diameter: 4mm  
 2. Material: Polyester



### Volleyball Net (high-grade)

Model: PQ15  
 1. Specification: 9500mm×1000mm  
 wire hole 100mm×100mm  
 2. Material: Polyethylene PE, tarpaulin, with four edges

# Table Tennis

## Ball Equipment Series



### Foldable Table Tennis Table I

Model: TQW0844

1. Comply with QB/T2700-2005 standard
2. Table top: With indoor special ball board medium fiber density board, the board thickness is 18mm. With the panel rainbow MDF+ cyanogen veneer process, the color is new blue, which has waterproof and anti-oil effect, no irritating odor, scratch resistant and easy to clean.
3. PVC edges are used on all sides, the table has a white edge with a width of 20mm, the middle line is 3mm, the flatness is  $\leq 4$ mm, the elasticity is 220-260mm, the elasticity uniformity is  $\leq 15$ mm, the surface gloss is  $\leq 10$ ; mesa friction coefficient is  $\leq 0.7$ .
4. Around the table, 25mm\*50mm high-quality steel pipe is used to make the skirt bracket, equipped with plastic corner protection to ensure the flatness.
5. Foot: 30\*60mm\*1.5mm high quality steel pipe, with arch design structure principle. It contains moving casters, which can be retracted to ensure the bearing capacity of the arch. The small arch folds small on the table top, the big arch folds again, the color is red, and the joint of the footing and the ground and the countertop has multiple height adjustment functions.
6. The whole table expansion size: 2740\*1525\*760mm,
7. Application: Used in training and professional competitions
8. Weight of the whole table:  $\geq 115$ kg



### Table Tennis Scoreboard

Model: TQW0836

1. Specification: 1400mm×750mm
2. Material: Steel shell, special cardboard core sheet



### Table Tennis Referee Tool Holder

Model: TQW0835

1. Specification: 118mm×70mm
2. Material: Equipped with red, yellow and white cards, a ruler and an edge picker, necessary for the referees



### Foldable Table Tennis Table II

Model: TQW0845

1. Table top: With indoor special ball board medium fiber density board, the board thickness is 25mm. With cyanogen veneer process, the color is new blue, which has waterproof and anti-oil effect, no irritating odor, scratch resistant and easy to clean.
2. PVC edges are used on all sides, the table has a white edge with a width of 20mm, the middle line is 3mm, the flatness is  $\leq 4$ mm, the elasticity is 220-260mm, the elasticity uniformity is  $\leq 10$ mm, the surface gloss is  $\leq 10$ ; mesa friction coefficient is  $\leq 0.4$ .
3. Around the table, 25mm\*50mm high-quality steel pipe is used to make the skirt bracket, equipped with plastic corner protection to ensure the flatness.
4. Foot: adopts the arch structure of Zhaozhou Bridge. It is an arch bridge floor structure, containing stable steel frame to ensure the bearing force of the arch. The surface is welded with high-quality steel plate as a whole, with the thickness  $\geq 50$ mm. The color is red, and the joint of the footing and the ground and the table top has multiple height adjustment functions.
5. The whole table expansion size: 2740\*1525\*760mm,
6. Application: Used in training and professional competitions
7. Weight of the whole table:  $\geq 200$ kg



### Table Tennis Net Rack

Model: TQW0834

1. Specification: Post height 152.5mm+2mm, Distance to table-board 152.5mm+/-3mm
2. Material: Spiral mounting, accurate and reliable, easy installation, high tension force of the rack, clamping firmly. Equipped with net and net measurer.



### Table Tennis Net

Model: PPQ17

1. Specification: 1740mm $\pm$ 20mm
2. Material: Using polyethylene woven network wire, increase the ability to beat, enhance the service life.



### Outdoor Table Tennis Table

Model: TSQL3038

1. Specification: 2740mm×1572mm×914mm
2. Material: Table board: SMC (sheet-shaped molded reinforced plastic) one-step compressing moulding under high temperature. The net is made of 2mm thick steel plate. The bottom of table board is made of "well" grid stiffener structure. The support frame of each half board is designed with 4 vertical 4 horizontal support connections, the level of the table can be adjusted. Suitable for training.



### Table Tennis Table

Model: TSTQ2396

1. Specification: 2740mm×1525mm×760mm
2. Material: Movable table leg is made of 40mm×40mm×2mm high-strength steel pipe. Suitable for training and fitness.

### The Hoarding for Table Tennis Venue

Model: TQW0841

1. Specification: 1400mm×750mm
2. Material: Steel frame, high intensity oxford cloth.



### Table Tennis Chief Referee's Chair

Model: TQW0837

1. Specification: Packing size 1680mm×700mm×390mm
2. Material: Foldable, lightweight, easy to carry, use for competition.



### Table Tennis Second Referee's Chair

Model: TQW0838

1. Specification: 450mm×450mm×1200mm
2. Material: Use for competition

# Badminton

## Ball Equipment Series



### Badminton Net Poles (movable)

Model: TSTQ3005

1. Specification: Central height of net: 1524mm, with both ends not exceeding 26mm above the central height.
2. Material: High quality carbon steel



### Badminton Net Poles II

Model: TQW0352A

1. Specification: 80kg
2. Material: Casting Iron



### Badminton Net Poles (buried)

Model: TSTQ3004

1. Specification: 6190mm×45mm×1550mm
2. Material: High quality carbon steel



### Movable Net Poles for Volleyball and Badminton

Model: TQ2307

1. Specification: 12970mm × 670mm × 1454/1664/1920/2120mm
2. Material: It is used for volleyball and badminton competitions at schools and youth clubs.



### Badminton Net Poles III


Model: TSW0352

1. Specification: 100kg
2. Material: Steel welding




### Badminton Net Poles I

Model: TB-YPW-006  
1. Specification: 55kg  
2. Material: Steel casting iron



### Badminton Scoreboard

Model: TQW035  
1. Specification: 1730mm×850mm×660mm  
2. Material: Steel frame, PVC board



### Badminton Net

Model: TQW353  
1. Specification: 6100mm×760mm  
2. Material: Ageing-resistant Polyester



### Badminton Net Height Measurer

Model: TQW0456  
Material: Aluminum alloy



### Badminton Referee Chair I

Model: TYC-009  
1. Specification: 1470mm×850mm×2040mm,  
Seat height 1530mm  
2. Material: Fully constructed with aluminum alloy  
profiles, featuring rear-mounted rubber wheels for  
quick mobility.




### Badminton Referee Chair II

Model: TB-YPW-009A  
1. Specification: 900mm×900mm×1700mm  
2. Material: Steel

# Tennis

## Ball Equipment Series



### Fully Movable Tennis Post

Model: TYZ-010

1. Specification: 13140mm×1000mm×1070mm
2. Material: Made of mold-pressed aluminum alloy, can be moved in all directions and used on multifunctional courts.

### Steel Bench

Model: TY-011L

1. Specification: 2000mm×470mm×420mm
2. Material: Made of refined steel structure.



### Aluminum Alloy Bench I

Model: TY-016

1. Specification: 1995mm×725mm×765mm
2. Material: Fully made of aluminum alloy.



### Aluminum Alloy Bench II

Model: TY-014L

1. Specification: 2170mm×1150mm×1995mm
2. Material: Fully made of aluminum alloy.



### Aluminum Alloy Bench (with Shed)

Model: TY-019P

1. Specification: 1960mm×875mm×1950mm
2. Material: PC shading plate for long-term outdoor use. The surface is coated with super weather resistant pure polyester powder, without screw plate, durable.





### Tennis Referee Chair

Model: TCY-809

1. Seat height 2100mm, international standard size.
2. Overall size: 1700mm×900mm×3250mm
3. Material: Fully made of aluminum alloy, the base uses perforated plate. The chair legs are equipped with high elasticity rubber pads, dual umbrella plughole design.



### Tennis Net (Single String)

Model: TW-001

1. Specification: 12800mm×1070mm
2. Mesh: 40mm×40mm, wire diameter φ2.5mm
3. Material: PE braided rope, resistant to acids/alkali, anti-aging, and impact-resistant with long service life. Edging made of PVC material, quadruple-stitched for durability.

### Tennis Net (Double String)

Model: TW-002

1. Specification: 12800mm×1070mm
2. Mesh: 35mm×35mm, wire diameter φ3mm
3. Material: PE braided rope, acid/alkali-resistant, with PVC-reinforced top edging quadruple-stitched for durability. The six-cell double-layer reinforced design at the top enhances net strength, preventing ball breakthrough during high-speed tennis play, fully compliant with international premium tournament standards.



### Fully Movable Tennis Post

Model: TBLJB-1004


1. Specification: 310kg
2. Material: Fully made of aluminum alloy.



### Straight Tennis Post

Model: TYZ-006

1. Specification: 80mm×80mm; Thickness: 4mm
2. Post Height: 1435mm
3. Embedded Depth: 367mm
4. Material: Made of reinforced aluminum alloy with precision worm and turbo type tightening device.



### Singles Support Rod

Model: TDZ-16

1. Specification: Height 1065mm
2. Material: Fully made of aluminum alloy, 304 stainless steel screws, adjustable height.



### Tennis Scoreboard I

Model: TQW0412  
 1. Specification: 1200mm×500mm×1750mm  
 2. Material: Aluminum alloy



### Tennis Scoreboard II

Model: TQW0413  
 1. Specification: 1195mm×422mm×1980mm  
 2. Material: Steel frame, PVC fop

### Wind Blocking Fence

Model: TFW-028A  
 1. Specification: 2000mm×18300mm  
 2. Material: PE wiredrawing woven, with PVC covered edge, acid and alkali resistance, moistureproof, strongly heat-resistance, chemical stability, long service life, strong weather resistance, windbreak rate 60% to 70%.



### Sponge Roller

Model: TXS-32  
 1. Specification: 1500mm×860mm×920mm  
 2. Material: Made by aluminum alloy, high absorbent with imported sponge.






### Tennis Court Squeegee

Model: TQW0386  
 1. Specification: 1500mm×860mm×920mm  
 2. Material: Thickened 9mm strips, larger ground covering area, push water more thoroughly. The use of directional wheel design solves the problem of swaying left and right, free handing design, easier to change the strips.

# Padel

## Ball Equipment Series



### Summary of Court

Model: TQC1003A/ TQC1003B

1. Size: 20m×10m (L\*W)

2. Component:

2.1 Column and Mesh	2.2 Tempered Glass
2.3 Artificial Turf	2.4 Light System
2.5 Pole with net	





## Column and Mesh

1. Column (Hot dip galvanized tube)
  - 1.1 Corner column & main Cross-bar  
Adopts 100mm×100mm×3mm high quality steel tube.
  - 1.2 Other columns  
Adopts 100mm×50mm×3mm high quality steel tube.
2. Mesh (Galvanized steel wire mesh)
  - 2.1 Mesh frame  
Adopts 50mm×30mm×2mm high quality steel tube.
  - 2.2 Height  
Ends and both sides: 4m (3m glass +1m mesh)  
Middle of sides: 3m
  - 2.3 Mesh size  
Wire diameter: 4mm  
Mesh distance: 45\*45mm
3. Color: can be customized

## Artificial Turf

1. Pile Height: 12mm
2. Dtex: 6500
3. Density: 42000 stiches/m<sup>2</sup>
4. Backing: PP+ Net
5. Coating: SBR
6. Color: Blue or Green
7. Qty: 205m<sup>2</sup>
8. Roll size :
  - 4\*10m 2 rolls
  - 4\*12m 2 roll
  - 2\*14.5m 1 roll
9. UV resistance PE monofilament yarn.



## Tempered Glass

1. Type : Explosion-proof , Tempered glass
2. Dimension : 2m×3m(W\*H)
3. Thickness: 12mm
4. Qty : 18 pcs
5. Package: wooden carton
6. GW: 3240kgs



## Light System

1. Light Column
  - 1.1 Height: 6m
  - 1.2 Material: Galvanized Steel tube with 100\*50\*3mm for lower and 50×50×3mm for upper.
2. Light
  - 2.1 Power supply voltage: AC180-240V
  - 2.2 System power: 200W/pc
  - 2.3 Qty: 8pcs (2 pcs for each column)



## Pole with Net

1. Net
  - 1.1 Net Size: 10m(L)\*920mm(H)
  - 1.2 Material: PE net with PVC cloth
  - 1.3 Mesh hole: 45mm
  - 1.4 Net color : Black
2. Pole
  - 2.1 Height: 970mm
  - 2.2 Material: Square steel tube with 100×50×3mm



## Racket

1. Material: 50% Carbon
2. Length: 46.5cm
3. Weight: 365+-10g

### Shape Available

Material: 100% Carbon  
3k, 12k, 18k



Item	Padel	Padel Pro	Padel Pro S
Size	2.5 inch	2.5 inch	2.5 inch
Weight	56-59.4g	56-59.4g	56-59.4g
Rebound	1.35-1.47M	1.35-1.47M	1.35-1.47M
Material	20% domestic wool, natural rubber.	45% TTI wool, natural rubber.	57% TTI wool, natural rubber.

# LED Display

## Ball Equipment Series

### LED Indoor Display Main Technical Parameters

Models	PH1.6 Full color	PH1.9 Full color	PH2.5 Full color	PH3 Full color	PH4 Full color	PH4.572 Full color	PH5 Full color	PH6 Full color	PH7.62 Full color	
Unit Module	Pixel Pitch (mm)	1.6	1.9	2.5	3	4	4.572	5	6	7.62
	Module Size (mm)	240×240	240×240	240×240	192×192	160×160	146×146	160×160	192×192	244×122
	Physical Density (Dots / m <sup>2</sup> )	360000	275625	160000	111111	62500	47839	40000	27777	17222
	Glowing Point Color				1R 1G 1B					
	LED Package	SMD1010	SMD1010	SMD2121	SMD2121	SMD2121	SMD3528	SMD3528	SMD3528	
	Module Resolution	144×144	126×126	96×96	64×64	40×40	32×32	32×32	32×16	
	Module Powe	56W	58W	40W	42W	40W	30W	30Wv	20W	
	Best Viewing Distance	1.7m	2m	2.5m	4m	5m	6m	6m	7m	8m
Main Technical Parameters	Best View Angle	120°	120°	120°	120°	120°	120°	120°	120°	120°
	Maximum Power (W / m <sup>2</sup> )	168	175	120	1200	1600	1400	1200	1000	650
	Cabinet Resolution	288×288	252×252	192×192	128×128	160×160	128×128	128×128	128×128	128×96
	Box Size (mm)	480×480	480×480	480×480	384×380	640×640	585×585	640×640	768×768	976×732
	Box Weight (kg)	11	11	11.5	15	32	30	32	40	32
	Power Supply	MBI5024, MBI5036, MBI5042 etc (16-Channel Constant Current LED Driver)								
	Drive Way	1/24 Scan Constant Current Rive	1/16 Scan Constant Current Drive	1/8 Scan Constant Current Drive						
	Frame Change Frequency	≥60Hz/s								
	Refresh Frequency	≥2000Hz/s		≥3200Hz/s		200Hz/s~1000Hz/s				
	White Balance Brightness (CD/ m <sup>2</sup> )	≥800	≥800	≥1600	≥1800	≥2000	≥2000	≥1800	≥1500	≥1100
	Working Environment Temperature and Humidity	-10°C ~+45°C /10-90%RH								
	Working Voltage	220 ± 10% or 380 ± 10% (Three-phase Five-wire System)								
	Grayscale / Color	280 Trillion Colors ≥ Display ≥ 10 7M Colors								
	Brightness Adjustment	RGB 0-100 Linearly Adjustable								
	Input Signal RF	RF,S-VIDEO.RGBHV.YUV.YC & Composition etc								
	Control System	Synchronous or Asynchronous Control System								
	MTBF	≥5000 hours								
	Life	≥100000 hours								
	Failure Point	< 0.0001								


### Outdoor LED Display Main Technical Parameters

Models	PH6 Full-color	PH10 Full-color	PH10 Double Colors (monochromatic)	PH12 Full color	PH16 Full color	PH16 Double Colors (monochromatic)	PH20 Full color	PH20 Double Colors (monochromatic)	PH25 Full color									
Unit Module	Pixel Pitch (mm)		10	10	12	16	16	20	20	25								
	Module Size (mm)	192×192	160×160	160×160	192×192	256×128	256×128/256	320×160	320×160	200×200								
	Physical Density (Dots / m <sup>2</sup> )	27777	10000	10000	6944	3906	3906	2500	2500	1600								
	Glowing Point Color	1R 1G 1B	1R 1G 1B	1R 1G	1R 1G 1B	1R 1G 1B	2R 1G	1R 1G 1B	2R 1G	1R 1G 1B								
	LED Package	SMD3535	SMD346	SMD346	SMD346	SMD546	SMD546	SMD546	SMD546	SMD546								
	Module Resolution	32×32	16×16	16×16	16×16	16×8	16×8	16×8	16×8	8×8								
	Module Powe	30W	20W	12W	20W	40W	30W	40W	30W	20W								
	Best Viewing Distance	7m	10m	10m	12m	14m	14m	17m	17m	23m								
Main Technical Parameters	Best View Angle	120°	110°	110°	110°	110°	110°	110°	110°	110°								
	Maximum Power (W / m <sup>2</sup> )	1000	900	500	650	1200	300	800	500	430								
	Cabinet Resolution	96×96	64×64	64×48	64×48	64×48	64×48	64×48	64×48	48×40								
	Box Size (mm)	576×576	640×480	640×480	768×576	1024×768	1024×768	1280×960	1280×960	1200×1000								
	Box Weight (kg)	32	40	40	40	60	60	80	80	80								
	Power Supply	MBI5024, MBI5036, MBI5042 etc (16-Channel Constant Current LED Driver)																
	Drive Way		1/2 or 1/4 scan constant current drive			Static drive												
	Frame Change Frequency	≥60Hz/s																
	Refresh Frequency	200Hz/s~1000Hz/s																
	White Balance Brightness (CD/ m <sup>2</sup> )	≥5500	≥5000	≥4500	≥4500	≥7000	≥6000	≥5300	≥4500	≥4500								
	Working Environment Temperature and Humidity	-10°C ~+45°C /10-90%RH																
	Working Voltage	220 ± 10% or 380 ± 10% (Three-phase Five-wire System)																
	Grayscale / Color	Gray/color 280 trillion color ≥ Display ≥ 10 7M color																
	Brightness Adjustment	RGB 0-100 Linearly Adjustable																
	Input Signal RF	RF,S-VIDEO.RGBHV.YUV.YC & Composition etc																
	Control System	Synchronous or asynchronous control system																
	MTBF	≥5000 hours																
	Life	≥100000 hours																
	Failure Point	< 0.0001																

## Transparent Borderless 24-second Timer

Model: TSW-1002A

1. Specifications: 680mm×110mm×570mm
2. Function: Full time, 24 seconds offense.
3. Accessories: Console, cable×2, display×2, optional wireless control, tripod, etc.



## Single-sided 24-second Timer

Model: TSW-1001A

1. Specifications: 600mm×500mm×150mm
2. Function: Full time, 24 seconds offense.
3. Accessories: Console, cable×2, display×2, optional wireless control, tripod, etc.



## Three-sided 24-second Timer

Model: TSW-1001B

1. Specifications: 600mm×500mm×150mm
2. Function: Full time, 24 seconds offense.
3. Accessories: Console, cable×2, display×2, optional wireless control, tripod, etc.



## Four-sided 24-second timer

Model: TSW-1001C

1. Specifications: 600mm×500mm×150mm
2. Function: Full time, 24 seconds offense.
3. Accessories: Console, cable×2, display×2, optional wireless control, tripod, etc.



## Scoreboard III

Model: TSW-1002F

1. Specifications: 5000mm×1700mm×70mm (size can be customized)
2. Function: Display team name, scores, fouls (comparisons), suspend count, innings, possession of balls, full time, 24 seconds, 4 innings scores, fouls of 2 teams.
3. Accessories: Display×1, console×1, cable×1, highpower remote controller×2



## Scoreboard I

Model: TSW-1002B

1. Specifications: 1000mm×600mm×70mm
2. Function: Display team name, scores, fouls (comparisons), possession of balls, full time.
3. Accessories: Display×1, tripod×1, high-power remote controller×1



## Scoreboard II

Model: TSW-1002C

1. Specifications: 2400mm×1200mm×70mm
2. Function: Display team name, scores, fouls (comparisons), suspend count, innings, possession of balls, full time, 24 seconds, 4 innings scores.
3. Accessories: Display×1, console×1, cable×1



## Scoreboard IV

Model: TSW-1002H

1. Specifications: 1800mm×900mm×70mm
2. Function: Team name, scores, fouls (comparisons), suspend count, innings, possession of balls, full time, 24 seconds.
3. Accessories: Display×1, console×1, cable×1
4. Optional: Stand, wooden case, wireless control

### Football Scoreboard

Model: TSW-1005


1. Specifications: 1800mm×900mm×70mm
2. Function: Display of team name, round, scores, playing time.
3. Accessories: Display×1, high-power remote controller×1
4. Optional: Stand, wooden case



### Serving Display

Model: TSW-1008

1. Specifications: 405mm×260mm×50mm
2. Function: Display possession of balls.
3. Accessories: Display×1, power adapter×1



### Football Substitution Cards

Model: TSW-1004



### Time Clock

Model: TSW-1006



### Backboard LED Strip

Model: TSW-1012

1. Specifications: 1700mm×920mm×70mm (2 sets)
2. Application: For 24-second countdown.



### Competition-grade Light Strip

Model: TQ1471

Specifications: Dual-color light strip, compliant with FIBA requirements.  
1 set per backboard.



### Basketball Time Out Siren

Model: TSW-1013



### Volleyball Time Out Siren

Model: TSW-1014



### Trihedral Team Foul Display

Model: TSW-1015B

# Venue Seat Series

## Ball Equipment Series

### Telescopic Tribune Series

- ◇ Manual Low-back stadium telescopic tribune



**81001** TSCG-KTY-A1



- ◇ Electric Low-back stadium telescopic tribune

**81002** TSCG-KTY-A2

Layer width	850mm
Layer height	310mm
Pedal material	Wood plate, Iron plate, Aluminum plate
Seat Type	Low-Back Stadium Chair
Seat pitch	480mm
Folding modes	Manual or Electric



- ◇ Manual front-mounted stadium telescopic tribune



**81003** TSCG-KTY-B1




- ◇ Electric front-mounted stadium telescopic tribune

**81004** TSCG-KTY-B2

Layer width	850mm
Layer height	310mm
Pedal material	Wood plate, Iron plate, Aluminum plate
Seat Type	Low-Back Stadium Chair
Seat pitch	480mm
Folding modes	Manual or Electric
Flip Mode	Manual






◇ Electric front-mounted telescopic tribune



**81004 TSCG-KTY-B3**

Layer width	850mm
Layer height	310mm
Pedal material	Wood plate, Iron plate, Aluminum plate
Seat Type	Hollow plastic folding chair w/o handrails
Seat pitch	500mm
Folding modes	Manual or Electric
Flip Mode	Auto



◇ Manual front-mounted soft telescopic tribune


**81005 TSCG-KTY-C1**



◇ Electric front-mounted soft telescopic tribune

**81006 TSCG-KTY-C2**

Layer width	850mm
Layer height	310mm
Pedal material	Wood plate, Iron plate, Aluminum plate
Seat Type	Soft sponge chair w/ handrails
Seat pitch	500mm
Folding modes	Manual or Electric
Flip Mode	Manual






◇ Manual back-mounted stadium telescopic tribune

**81007** TSCG-KTY-D1

◇ Electric back-mounted stadium telescopic tribune

**81008** TSCG-KTY-D2

Layer width	850mm
Layer height	310mm
Pedal material	Wood plate, Iron plate, Aluminum plate
Seat Type	Front-mounted hollow plastic chair w/o handrails
Seat pitch	500mm
Folding modes	Manual or Electric
Flip Mode	Manual or Automatic




◇ Manual back-mounted stadium telescopic tribune with handrail

**81009** TSCG-KTY-E1

◇ Electric back-mounted stadium telescopic tribune with handrail

**81010** TSCG-KTY-E2





◇ Manual-The hollow bench telescopic tribune

**81011 TSCG-KTY-F1**

◇ Electric-The hollow bench telescopic tribune

**81012 TSCG-KTY-F2**

Layer width 850mm

Layer height 310mm

Pedal material Wood plate, Iron plate, Aluminum plate

Seat Type Hollow benches

Seat pitch 470mm

Folding modes Manual or Electric

Flip Mode Manual or Automatic



◇ Fixed Tribune

**83001 TSCG-KTY-H1**

Layer width 850mm




Layer height 310mm

Pedal material Wood plate, Iron plate, Aluminum plate

Seat Type Optional

Seat pitch 480mm

Folding mode Fixed



## Fixed Seats Series

### Seat Types

Hollow plastic chair without back

80001 TSCG-KTY-Y001



Mid-back hollow plastic chair

80003 TSCG-KTY-Y003A




High-back hollow plastic chair

80005 TSCG-KTY-Y004



Low-back hollow plastic chair

80002 TSCG-KTY-Y002



Mid-back hollow plastic chair

80004 TSCG-KTY-Y003B



Front-mounted folding chair

80006 TSCG-KTY-Y005



Hanging hollow plastic chair

80007 TSCG-KTY-003



Floor-to-ceiling hollow plastic chair

80009 TSCG-KTY-005



Straight hollow plastic folding chair

80011 TSCG-KTY-007



Straight hollow plastic turnover chair

80013 TSCG-KTY-009



Straight hollow plastic chair

80008 TSCG-KTY-004



Movable hollow plastic chair

80010 TSCG-KTY-006



Hanging hollow plastic turnover chair

80012 TSCG-KTY-008



Straight hollow plastic turnover chair

80014 TSCG-KTY-010



## ● Hollow Seat Installation

### • Front mounted seat installation

Connect to the stamped steel piece with sprayed surface.



### • Hanging seat installation

Connect the Φ32mm tube to the die cast aluminum alloy hanging bracket with sprayed surface.




### • Straight seat installation

Connect the Φ32mm tube to the die cast aluminum alloy vertical bracket with sprayed surface.



### • Movable seat installation

Connect the 60mm\*40mm rectangular tube to the oval column bracket with sprayed surface.



### ◇ Aluminum movable stands

**83003 TSCG-KTY-H2**

Layer width	700mm
Layer height	200mm
Plate width	240mm
Plate thickness	3mm



### ◇ Aluminum alloy stage

**84001 TSCG-WT-A**

Name	Aluminum alloy stage
Material	Aviation aluminum alloy 6061-T6
Specification	1220×1220mm
Load capacity	500kg/cm <sup>2</sup>
Height	0.6m, 0.8m, 1m, 1.2m (adjustable)



Aluminum alloy stage structure



## III Deluxe Soft Seat Series

Deluxe soft seat

82001 TSCG-RB-660



Deluxe soft seat

82002 TSCG-RB-690



Deluxe soft seat

82004 TSCG-RB-510



Deluxe soft seat

82006 TSCG-RB-1120



Deluxe soft seat

82008 TSCG-RB-630



Deluxe soft seat

82009 TSCG-RB-700



Deluxe soft seat

82010 TSCG-RB-650




Deluxe soft seat

82012 TSCG-RB-670



Color and material options



Color and material options



## III Deluxe Soft Seat Series



### ● Maple wood grades

Name

Taishan maple wood sports flooring

Specifications

Canadian maple wood and Russian birch



Grade A wood flooring has the highest quality and the smallest color difference. It has no flaws, such as knots, bug holes, sap holes, or cores. The patterns are same on both sides. Each piece is flat, and has same width on either side and cracks that are no deeper or longer than 1/5 of the thickness and length of the piece itself. The angle of the lines of the pattern on each piece is smaller than 10°. The surface is smooth without corrosion.

A grade B wood flooring panel is made of the parts that are close to the bark and the core and not significantly different from a grade A wood flooring panel in terms of quality. The deeper the color, the bigger the color difference and the knots. Grade B wood flooring is finished with baked paint for even color shades and better look.

### • Plank Flooring


1. Panels are made of 22mm thick solid hardwood, including Manchurian ash tree, beech, rubber wood, maple wood, mahogany, and Mongolian oak.
2. Panel size: 22mm×550mm×2180mm; easy for transportation.
3. The special flexible locking and clamping system allows for safe and quick installation.
4. Complied with EN 14904 A4 and approved by FIBA.



### • Imported Steel Keel Structure

FIBA approved | DIN standard


This structure has been approved by FIBA and passed DIN standard test. Its steel keel and base flooring provide excellent flexibility and shock absorption. The integrity and rigidity of the structure allow the flooring to have even performance and give athletes better protection. It is suitable for large events such as professional training and competitions, exhibitions, and performance.



### • Single-layer Keel Structure

FIBA approved | DIN standard

This structure has been approved by FIBA and passed DIN standard test. Its single-layer pine wood keel and base flooring provide excellent flexibility and shock absorption. The integrity and rigidity of the structure allow the flooring to have even performance and give athletes better protection. It is suitable for large events such as professional training and competitions, exhibitions, and performance.



### • Double-layer Keel Structure

FIBA approved | DIN standard

The double-layer keel structure can be installed on various venue conditions and provide excellent flexibility and shock absorption. The integrity and rigidity of the structure allow the flooring to have even performance and meet user's expectations for performance, look, and durability. The shock absorption of this structure is one of its kind and the performance is outstanding like no other. It meets the requirements for all types of training and international competitions.



### Canadian Maple Wood

From materials to production, hundreds of steps are managed with details and standards. We select the best materials possible and customize to your needs for sports courts of different sizes and specification using maple wood flooring in highest quality.



### Imported Maple Wood Lumber

We have large quantity of imported maple wood lumber in stock. Maple wood is the best option for sports court flooring due to its outstanding performance, durability and strength compared with other types of wood. It can fulfill all sorts of sporting requirements and provide better protection to athletes.



### Advanced Domestic Production Line

Premium material like maple wood lumber deserves advanced manufacturing equipment and high standards. Taishan Sports has its own sporting wood flooring company where each wood panel is made with German high precision equipment and inspected to ensure high standard.



#### • Plank Flooring (PRO)

Triple-layer structure: special flexibility and shock absorption.  
Suitable for top level competitions (basketball and handball).  
Total height: 44mm, including 10mm foam base and 12mm plywood.




#### • Plank Flooring (PRO V2)

Triple-layer structure: special flexibility and shock absorption.  
Suitable for fast pace ball games.  
Total height: 39mm.



#### • Plank Flooring (PRO V2+)

The LVL keel system has height adjusting pads.  
Can be installed on uneven concrete surface.  
Total height: 122mm to 164mm.




## Floor series ||

### Outdoor Basketball Court Flooring

#### TS-FS001 / Training

1. Size: 30.48cm×30.48cm×1.3cm
2. Shock absorption: 20% - 50%
3. Vertical deformation:  $\leq 3\text{mm}$
4. Tensile strength:  $\geq 0.7\text{MPa}$
5. Tear strength:  $\geq 5\text{kN/m}$



### Indoor Badminton Court Flooring

#### TS-FS002 / Competition

1. Size:  $7.0\text{mm} \pm 0.1\text{mm}$
2. Shock absorption:  $\geq 20\%$
3. Tensile strength:  $\geq 0.5\text{MPa}$
4. Color difference ( $\Delta E$ ) after aging for at least 360 days based on GB/T8424.1-2001:  $<0.5$

#### TS-FS003 / Club training

1. Vertical deformation:  $0.6 - 3.0\text{ mm}$
2. Anti-slip rating: 80 - 110
3. Elongation at break:  $\geq 40\%$



### Indoor Table Tennis Flooring

#### TS-FS006 / Competition

1. Size:  $7.0\text{mm} \pm 0.1\text{mm}$
2. Shock absorption:  $\geq 20\%$
3. Tensile strength:  $\geq 0.5\text{MPa}$
4. Color difference ( $\Delta E$ ) after aging for at least 360 days based on GB/T8424.1-2001:  $<0.5$

## Indoor Tennis Court Flooring

TS-FS007 / Club training


1. Size:  $5.0\text{mm} \pm 0.1\text{mm}$
2. Vertical deformation:  $0.6 - 3.0\text{ mm}$
3. Anti-slip rating:  $80 - 110$
4. Elongation at break:  $\geq 40\%$



## Outdoor Tennis Court Flooring


TS-FS008 / Competition

1. Size:  $30.48\text{cm} \times 30.48\text{cm} \times 1.3\text{cm}$
2. Shock absorption:  $20\% - 50\%$
3. Vertical deformation:  $\leq 3\text{mm}$
4. Tensile strength:  $\geq 0.7\text{MPa}$
5. Elongation at break:  $\geq 90\%$
6. Tear strength:  $\geq 5\text{kN/m}$



TS-FS009 / Club training

1. Size:  $30.48\text{cm} \times 30.48\text{cm} \times 1.3\text{cm}$
2. Shock absorption:  $20\% - 50\%$
3. Vertical deformation:  $\leq 3\text{mm}$
4. Tensile strength:  $\geq 0.7\text{MPa}$
5. Elongation at break:  $\geq 90\%$
6. Tear strength:  $\geq 5\text{kN/m}$



## Indoor Table Tennis Flooring

TS-FS004 / Competition

1. Size:  $7.0\text{mm} \pm 0.1\text{mm}$
2. Shock absorption:  $\geq 20\%$
3. Tensile strength:  $\geq 0.5\text{MPa}$
4. Color difference ( $\Delta E$ ) after aging for at least 360 days based on GB/T8424.1-2001:  $< 0.5$

TS-FS005 / Club training

1. Size:  $5.0\text{mm} \pm 0.1\text{mm}$
2. Vertical deformation:  $0.6 - 3.0\text{ mm}$
3. Anti-slip rating:  $80 - 110$
4. Elongation at break:  $\geq 40\%$



## Indoor Volleyball Court Flooring


TS-FS10 / Competition

1. Size:  $7.0\text{mm} \pm 0.1\text{mm}$
2. Shock absorption:  $\geq 20\%$
3. Tensile strength:  $\geq 0.5\text{MPa}$
4. Color difference ( $\Delta E$ ) after aging for at least 360 days based on GB/T8424.1-2001:  $< 0.5$

## Gym Flooring

TS-FS012 / Professional


1. Size:  $7.0\text{mm} \pm 0.1\text{mm}$
2. Shock absorption:  $\geq 20\%$
3. Tensile strength:  $\geq 0.5\text{MPa}$
4. Color difference ( $\Delta E$ ) after aging for at least 360 days based on GB/T8424.1-2001:  $< 0.5$



## Indoor Volleyball Court Flooring

TS-FS11 / Club training


1. Size:  $5.0\text{mm} \pm 0.1\text{mm}$
2. Vertical deformation:  $0.6 - 3.0\text{ mm}$
3. Anti-slip rating:  $80 - 110$
4. Elongation at break:  $\geq 40\%$



### Gym Flooring

TS-FS013 / Club training

1. Size: 5.0mm ± 0.1mm
2. Vertical deformation: 0.6 - 3.0 mm
3. Anti-slip rating: 80 - 110
4. Elongation at break: ≥40%




Compound rubber

### Special Rubber Flooring for Gym Weight Area

TS-FS014 / Professional

1. Name: Compound rubber flooring
2. Specification: 1000×1000×20mm
3. Material: The 1.6mm thick rubber surface is made of EPDM particulate and high standard rubber powder. No peeling in 6 to 7 years. The base uses eco-friendly rubber particulate.



Starry rubber

### Special Rubber Flooring for Gym Weight Area

TS-FS015 / Club training

1. Name: Starry rubber flooring
2. Specification: 1000×1000×20mm
3. Material: The 1.6mm thick rubber surface is made of EPDM particulate and high standard rubber powder. No peeling in 6 to 7 years. The base uses eco-friendly rubber particulate.

# 03

## EVENT CASES

Gymnasium

85

Exhibitions

86

# Events & Exhibitions

## EVENT CASES



Badminton Venue - the 13th African Games in Ghana 2024

## ► Exhibitions



Saudi Sport Show 2024



Trade Fair in Morocco 2024



FSB Sports Show Riyadh 2025



Canton Fair (China Import and Export Fair) 2025

## ► Gymnasium



Alma-Ata Olympic Training Center 2024



Alma-Ata Multifunctional Ball Gym 2022



Egypt Sports Expo 2025



CHINA SPORT SHOW 2025

## **SHANDONG TAISHAN SPORTS EQUIPMENT CO., LTD.**

- 📞 Tel/WhatsApp: +86 18453178888
- 🌐 Web: [www.taishansports.cn](http://www.taishansports.cn)
- ✉️ Email: [info@taishansports.com](mailto:info@taishansports.com)
- 📍 HQ & Factory: No.1 Taishan Tiyu Rd, Laoling, Dezhou City, Shandong Province, China. 253600



TaiShan Sports



taishansports



TaiShan Sports